

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
27 December 2001 (27.12.2001)

PCT

(10) International Publication Number
WO 01/97696 A1

(51) International Patent Classification⁷: **A61B 17/128**,
17/122, 19/00, 18/14

(21) International Application Number: PCT/US01/19629

(22) International Filing Date: 19 June 2001 (19.06.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/212,420 19 June 2000 (19.06.2000) US

(71) Applicant: **IMAGE-GUIDED NEUROLOGICS, INC.**
[US/US]; 2290 Eau Gallie Boulevard, Melbourne, FL
32935 (US).

(71) Applicants and

(72) Inventors: **MAZZOCCHI, Rudy, A.** [US/US]; 241


Lansing Island Drive, Indian Harbor Beach, FL 32937 (US). **MILLER, Thomas, I.** [US/US]; 145 Elfin Street, Palm Bay, FL 32909 (US). **PARMER, Kari** [US/US]; 3199 Brentwood Lane, Melbourne, FL 32934 (US). **PARMER, Timothy, Alan** [US/US]; 3199 Brentwood Lane, Melbourne, FL 32934 (US). **SOLAR, Matthew, S.** [US/US]; 290 Normandy Drive, Indialantic, FL 32903 (US).

(74) Agent: **MCCRACKIN, Ann, M.**; Schwegman, Lundberg, Woessner & Kluth, P.O. Box 2938, Minneapolis, MN 55402 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW.

[Continued on next page]

(54) Title: SYSTEM AND METHOD OF MINIMALLY-INVASIVE EXOVASCULAR ANEURYSM TREATMENT



(57) Abstract: This document discusses an exovascular approach to treating an aneurysm using a minimally-invasive instrument guided by magnetic resonance imaging (MRI), computed tomography (CT), or another suitable imaging device. A trajectory guide entry device assists in targeting the aneurysm and determining the proper trajectory thereto. Examples of the aneurysm treatment device include a clip, a clasp, a snare, a loop, a hook, a staple, and an electrocautery or other electrode, or any combination of such devices. The aneurysm treatment device is delivered by a probe, such as a tube or other catheter.



WO 01/97696 A1



(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

SYSTEM AND METHOD OF MINIMALLY-INVASIVE EXOVASCULAR ANEURYSM TREATMENT

CROSS-REFERENCE TO RELATED APPLICATION

This patent application claims the benefit of priority, under 35 U.S.C. Section 119(e), to U.S. Provisional Patent Application Serial Number 60/212,420, entitled "METHOD OF MINIMALLY-INVASIVE ANEURYSM CLIPPING AND APPARATUS," filed June 19, 2000, the disclosure of which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

This document relates generally to minimally-invasive surgical systems, devices, and methods, and particularly, but not by way of limitation, to a system and method of minimally-invasive exovascular aneurysm treatment.

BACKGROUND

An aneurysm is an abnormal dilatation of a blood vessel. Brain aneurysms pose a particular risk of rupture and resulting hemorrhage, resulting in possible significant loss of brain function and even death. Autopsy studies have estimated that between about 1.5% and 8% of the population have intracranial aneurysms. Between 60,000 and 80,000 cerebral aneurysms are diagnosed annually in the U.S. Of these patients, about 20,000 to 30,000 are diagnosed following the occurrence of subarachnoid hemorrhage. The annual risk of an aneurysmal rupture is about 2%. Patients that experience aneurysmal rupture typically experience a mortality rate of about 50-60%. If the ruptured aneurysm is left untreated, about 25-35% of such patients will die of recurrent hemorrhage. For about 20-40% of those patients that do survive, the ruptured aneurysm results in a significant deficit in neurological function.

One conventional technique for treating a brain aneurysm uses standard open surgical intervention techniques. A craniotomy is performed to create a relatively large opening in the patient's skull. The surgeon uses conventional

surgical instruments to retract intervening brain tissue to expose the blood vessel at the aneurysm for direct visualization. With the aneurysm and associated blood vessel in view, the surgeon manipulates and treats the aneurysm using traditional surgical instruments to clip or staple either the body of the vessel or the neck of the aneurysm. Although such surgical clipping yields a high likelihood of procedural success, it is highly invasive. Therefore, it risks inducing associated brain trauma, thereby requiring a long recovery time. Moreover, a significant number of brain aneurysms are located very deep in the brain, rendering such conventional surgical techniques difficult.

Another technique for treating a brain aneurysm uses an endovascular approach. For example, a catheter may be introduced (e.g., near a subject's groin) through a blood vessel and advanced to the aneurysm. In one technique, a detachable coil is introduced through the endovascular catheter and "packed" into the interior of the aneurysm. This coil, which is usually constructed of stainless steel and/or platinum wire, is intended to interrupt the turbulent blood flow into the aneurysm. The resulting blood clots within the interior of the aneurysm. This reduces the risk of aneurysmal rupture. Another endovascular method of treating aneurysms uses a detachable balloon. The balloon is inflated with cyanoacrylates to occlude the interior of the aneurysm. Yet another endovascular method of treating aneurysms introduces an intravascular stent or graft that occludes the adjacent neck of an aneurysm sufficiently to interrupt blood flow into the aneurysm while maintaining continued flow through the native vessel.

These endovascular techniques for treating aneurysms, however, have not exhibited as high a likelihood of success as the open surgery techniques discussed above. Moreover, application of the endovascular techniques is generally limited to non-bifurcating, small-neck aneurysms, which actually constitute a small percentage of the clinically-diagnosed aneurysms. Furthermore, some aneurysms are exceedingly difficult to reach endovascularly because they require traversal of a long tortuous path through the accessing vessels. For these and other reasons, the present inventors have recognized a

need for improved techniques and associated devices for accessing and treating brain or other aneurysms.

SUMMARY

In contrast to the above-discussed open surgery and endovascular approaches to treating aneurysms, this document discusses a minimally-invasive exovascular approach to treating an aneurysm. Using such a minimally-invasive technique, the surgeon need only make a small opening for inserting an exovascular instrument to the aneurysm. In order to perform the treatment, the surgeon need not visualize the aneurysm directly. Instead, a magnetic resonance imaging (MRI), computed tomography (CT), or other suitable imaging device is provided to allow the surgeon to exovascularly guide a minimally-invasive aneurysm treatment device through the brain to the aneurysm, apply the treatment device to the desired portion of the aneurysm, and then remove the aneurysm treatment device. In a further example, an image-guided entry device is used to provide more accurate targeting and determination of a trajectory from the minimally-invasive entry opening to the aneurysm to be treated. The minimally-invasive techniques discussed in this document may permit more effective treatment of aneurysms that would be difficult to access or treat using endovascular techniques. Moreover, these minimally-invasive techniques may result in less shifting of brain tissue than open surgery techniques. This may permit more accurate targeting of the aneurysm, and less trauma to the intervening brain tissue.

In one example, this document discusses a system that includes an elongate exovascular probe. The probe includes proximal and distal ends. The probe also includes an outer dimension that is less than about 18 millimeters to permit the probe to be introduced through a similarly-sized minimally-invasive opening in a portion of a subject's skull and exovascularly advanced to an aneurysm within the skull. The system also includes an aneurysm treatment device carried by the probe. The aneurysm treatment device is dimensioned to permit the aneurysm treatment device to be introduced through the opening.

In another example, this document discusses a method of aneurysm

treatment. The method includes forming an opening in a subject's skull. The opening having a diameter that is less than or equal to the diameter of a burr hole. A probe is exovascularly inserted through the opening to an aneurysm using real-time or preoperative imaging to guide the probe to the aneurysm. An aneurysm treatment device is exovascularly introduced through a lumen in the probe to the aneurysm. Using the aneurysm treatment device, a morphology of the aneurysm is altered. Other aspects of the invention will be apparent on reading the following detailed description of the invention and viewing the drawings that form a part thereof.

10 BRIEF DESCRIPTION OF THE DRAWINGS

In the drawings, which are offered by way of example, and not by way of limitation, and which are not necessarily drawn to scale, like numerals describe substantially similar components throughout the several views. Like numerals having different letter suffixes represent different instances of substantially similar components.

Figure 1 is a schematic/block diagram illustrating generally an example of portions of a minimally-invasive aneurysm treatment system and portions of an environment in which it is used.

Figure 2 is a schematic/block diagram of another example of portions of an aneurysm treatment system, in which a distal tip of a catheter also includes a local imaging device for providing enhanced visualization of nearby regions, such as an aneurysm and nearby blood vessels and brain tissue or other structures.

Figure 3 is a schematic/block diagram of a further example of portions of an aneurysm treatment system, further including an entry device located at, in, and/or around an entry opening.

Figure 4 is a cross-sectional schematic diagram illustrating generally an example of a distal end of a catheter. Disposed in a retracted position within a lumen of the catheter is distal end of an example aneurysm treatment device.

Figure 5 includes several cross-sectional diagrams illustrating generally one technique for operating the aneurysm treatment device of Figure 4.

Figure 6 is a schematic illustration of several alternative components for aneurysm-clipping in an aneurysm treatment device.

Figure 7 is a cross-sectional schematic diagram illustrating generally another example of a distal end of a catheter, the distal end including a lumen
5 through which another example aneurysm treatment device is disposed for treating an aneurysm.

Figure 8 includes several cross-sectional diagrams illustrating another example of a distal portion of a snare-like aneurysm treatment device that includes a strand, the end of which has a normally-looped shape-memory
10 property.

Figure 9 is a perspective view illustrating another example of an aneurysm treatment device, which includes a pair of electrodes that are exovascularly delivered through a lumen of a catheter.

Figure 10 is a perspective view illustrating another example of an
15 aneurysm treatment device including a movable electrode and a fixed electrode.

Figure 11 is a perspective view illustrating another example of a catheter-delivered aneurysm treatment device, which in this case includes a C-channel clamp shaped for being fitted around an exterior portion of a blood vessel and clamping a desired portion of an aneurysm therebetween.

Figure 12 is a perspective view illustrating a number of possible variations of the minimally-invasive aneurysm treatment techniques discussed above, such as nasalpharyngeal access, frame-mounted entry devices, using a plurality of minimally-invasive devices, and/or using separate minimally-invasive devices for imaging and aneurysm treatment.
20

25 DETAILED DESCRIPTION

In the following detailed description, reference is made to the accompanying drawings which form a part hereof, and in which is shown by way of illustration specific embodiments in which the invention may be practiced. These embodiments are described in sufficient detail to enable those skilled in
30 the art to practice the invention, and it is to be understood that the embodiments may be combined, or that other embodiments may be utilized and that structural,

logical and electrical changes may be made without departing from the spirit and scope of the present invention. The following detailed description is, therefore, not to be taken in a limiting sense, and the scope of the present invention is defined by the appended claims and their equivalents.

5 In this document, the term “minimally-invasive” shall be interpreted as referring to techniques that are less invasive than conventional open surgical techniques that involve making a large enough opening to permit direct visual inspection of the internal surgical procedure. In particular, the term “minimally-invasive” is not restricted to the least-invasive technique possible.

10 Figure 1 is a schematic/block diagram illustrating generally an example of portions of a minimally-invasive aneurysm treatment system 100 and portions of an environment in which it is used. In this example, a portion of a top or side of a patient's skull 100 and scalp 102 are illustrated. A minimally-invasive entry opening 104 is created through skull 100 and scalp 102. In one example,
15 opening 104 is a substantially circular burr-hole having a diameter that is approximately between 8 millimeters and 18 millimeters, such as about 14 millimeters. A exovascular probe/tube/catheter 106 (or other rigid, semi-rigid, or flexible device) is inserted through opening 104, and is directed toward an aneurysm (e.g., a saccular, globular, giant, or other aneurysm) 108 associated
20 with blood vessel 110 within brain 112. Catheter 106 includes a lumen 114 extending between its proximal end 116 and its distal end 118. In one example, catheter 106 has an outer diameter that is less than the burr-hole diameter. In another example, catheter 106 has an outer diameter that is less than about 10 millimeters, such as an outer diameter of about 5 millimeters. In general, using a
25 smaller outer diameter value results in less trauma to the intervening tissue. In one example, catheter 106 has an inner (i.e., lumen) diameter that is approximately between 1 millimeter and 8 millimeters, such as about 3 millimeters.

 An aneurysm treatment device 120 is inserted through lumen 114 in
30 catheter 106. Aneurysm treatment device 120 includes a proximal end 122 and a distal end 124. Distal end 124 of aneurysm treatment device 120 includes a

device for altering a morphology of aneurysm **108**, such as to reduce the risk of its rupture. Such aneurysm treatments include, by way of example, but not by way of limitation, clipping, claspings, snaring, looping, hooking, stapling, applying electrical energy to diathermically heat and/or electrocauterize, grasping, retrieving, securing, and/or aspirating the contents of an aneurysm. The devices for performing such treatments may be mechanical, chemical and/or electromagnetic. The choice of an appropriate treatment will depend on the size, location, and type of aneurysm.

Because minimally-invasive opening **104** is generally too small to permit convenient direct visualization, this example of system **100** includes an alternative remote external imaging device **126** to assist the surgeon in guiding distal tip **118** of catheter **106** to aneurysm **108** while avoiding areas **128A-B** of brain **112**. In one example, imaging device **126** is a magnetic resonance (MR) imaging device and/or a computed tomography (CT) imaging device providing real-time and/or preoperative images for guiding catheter to aneurysm **108** and then treating aneurysm **108**. Such imaging modalities allow the surgeon to view images that include information about the three dimensional morphology of the aneurysm, the vessel associated with the aneurysm, and any nearby major and perforating vessels in and around the base of the aneurysm. The information yielded by such imaging modalities is advantageous for deciding whether and how to proceed with the aneurysm treatment, or for selecting a particular device or method for treating the aneurysm. In one example, an MR or CT imagable fiducial structure is positioned at a predetermined location at one or both of distal end **118** of catheter **106** and/or a distal end **124** of aneurysm treatment device **120** to create a locatable image for guiding and operating that particular device. The fiducial structure may produce either a positive image on the imaging modality or, alternatively, may be recognizable by producing a contrast with the image of the surrounding brain tissue.

Figure **2** is a schematic/block diagram of another example of portions of aneurysm treatment system **100** in which distal tip **118** of catheter **106** also includes a local imaging device **200** for providing enhanced visualization of

nearby regions, such as aneurysm **108** and nearby blood vessels and brain tissue or other structures. In one example, local imaging device **200** includes at least one microcoil for local MR imaging. Some suitable microcoil examples are described in: Truwit et al. U.S. Patent No. 5,964,705 entitled "MR-

5 COMPATIBLE MEDICAL DEVICES;" Kucharczyk et al. U.S. Patent Application No. 09/448,720, filed on November 24, 1999, entitled "MR-COMPATIBLE DEVICES;" Viswanathan et al. U.S. Patent Application No. 09/532,145, filed on March 21, 2000, entitled "A DEVICE FOR HIGH GAIN AND UNIFORMLY LOCALIZED MAGNETIC RESONANCE IMAGING;"

10 Viswanathan U.S. Patent Application No. 09/532,667, filed on March 21, 2000, entitled "A MICROCOIL DEVICE FOR LOCAL, WIDE FIELD-OF-VIEW AND LARGE GAIN MAGNETIC RESONANCE IMAGING;" and Viswanathan U.S. Patent Application No. 09/532,037, filed on March 21, 2000, entitled "A MICROCOIL DEVICE WITH A FORWARD FIELD-OF-VIEW

15 FOR LARGE GAIN MAGNETIC RESONANCE IMAGING." Each of these documents is incorporated herein by reference in its entirety, and also for their collective disclosure of microcoil examples and related techniques and their equivalents. In one example, one or more of such microcoils is molded into distal end **118** of catheter **106**, with appropriate connection wires extending

20 along the length of elongate catheter **106** to its proximal end **116** for coupling to imaging device **126** or other suitable device for delivering and/or receiving energy for performing the local imaging.

Such microcoils typically enhance the visual resolution of the imaging at the working distal end **118** of catheter **106** or other probe. This actively-visible

25 deployment probe improves the surgeon's ability to visualize the overall structure and position of the aneurysm as well as any branching capillaries or perforators that might be extending from the aneurysm or its vicinity. This can be important in ensuring effective treatment of the aneurysm. Moreover, such localized imaging allows the surgeon to avoid damaging such ancillary vessels,

30 thereby preserving needed blood flow through such vessels to surrounding tissue. Alternatively, it allows the surgeon to also provide similar or different

treatment to such ancillary vessels, where appropriate. In one example, imaging of ancillary vessels permits the surgeon to cauterize one or more of such vessels to avoid possible hemorrhaging and/or related complications.

Figure 3 is a schematic/block diagram of a further example of portions of system 100 further including an entry device 300 located at, in, and/or around minimally-invasive entry opening 104. In this example, ball-and-socket-type entry device 300 includes a stem-like cylindrical trajectory guide 302 that is used in conjunction with imaging device 126 to determine and lock-in a desired trajectory from opening 104 to aneurysm 108. Suitable examples of skull-mounted entry device 300, and ancillary devices and techniques for introducing a medical instrument such as catheter 106, are described in: Truwit et al. U.S. Patent No. 6,195,577 B1 entitled "METHOD AND APPARATUS FOR POSITIONING A DEVICE IN A BODY;" Truwit U.S. Patent Application No. 09/058,092, filed on April 9, 1998, entitled "TRAJECTORY GUIDE AND METHOD OF USE IN MAGNETIC RESONANCE AND COMPUTERIZED TOMOGRAPHIC SCANNERS;" Skakoon et al. U.S. Patent Application No. 09/828,451, filed on April 6, 2001, entitled "DEEP ORGAN ACCESS DEVICE AND METHOD;" Mazzocchi U.S. Provisional Patent Application No. 60/225,952, filed on August 17, 2000 entitled "IMPROVED TRAJECTORY GUIDES FOR SURGICAL INSTRUMENTS;" Skakoon et al. U.S. Patent Application No. 09/827,266, filed on April 5, 2001, entitled "MEDICAL DEVICE INTRODUCER." Each of these documents is incorporated by reference in its entirety, and particularly for their description of entry devices, trajectory guides, and ancillary devices and techniques and their equivalents.

Figure 4 is a cross-sectional schematic diagram illustrating generally an example of distal end 118 of catheter 106. Disposed in a retracted position within lumen 114 of catheter 106 is distal end 124 of an example aneurysm treatment device 120. In this example, aneurysm treatment device 120 includes a clip 400, an O-shaped ring 402 (or C-shaped partial ring), a wire-like retaining strand 404 snaring clip 400 (or other retention device), a middle tube 406 having a lumen 408 therethrough, and an inner tube 405 also having a lumen

therethrough through which a portion of strand **404** extends. In this example, clip **400** is a molded plastic clip having a normally-open shape-memory property. When it is pushed out of lumen **114**, such as by inner tube **405**, jaws **410A-B** of clip **400** spring open apart from each other such that clip **400** is in a substantially open position. Jaws **410A-B** are then positioned around a desired portion of aneurysm **108** (such as around a neck portion at which aneurysm **108** extends from vessel **110**, but leaving enough tissue to bridge the gap in the wall of the vessel created by the aneurysm). Then, jaws **410A-B** are closed around the desired portion of aneurysm **108**. In one example, this is accomplished by firmly holding retaining strand **404**, which is looped around a knob **412** or within a groove **414** of clip **400**, while pushing middle tube **406** out from lumen **114**. In this manner, middle tube **406** engages ring **402** and pushes ring **402** out around jaws **410A-B**. This closes jaws **410A-B** around the desired portion of aneurysm **108**, so that clip **400** is in its substantially closed position. Then, by manipulating the proximal end of retaining strand **404**, its looped distal end is pushed out slightly to open sufficiently to disengage retaining strand **404** from clip **400**, so that clip **400** is freed and left behind to clip the desired portion of aneurysm **108** to reduce its risk of rupture. In one example, inner tube **405** is optionally withdrawn to promote loosening and disengaging retaining strand **404** from clip **400**. Retaining strand **404**, middle tube **406**, inner tube **405**, and catheter **106** are then withdrawn from brain **112**, and minimally-invasive opening **104** is closed. Figure **5** includes several cross-sectional diagrams illustrating generally one technique for operating this example of aneurysm treatment device **120** of Figure **4**.

The example illustrated in Figures **4** and **5** includes many variations within its scope. In one such variation, retaining strand **404** includes a third strand extending through lumen **114** and coupled to a collar around the illustrated looped pair of strands of retaining strand **404**. By tightening or loosening the collar by manipulating the third strand, the loop is more securely opened or closed to respectively release or retain clip **400**. In another example, retaining strand **404** (which need not be a loop, but is alternatively a single

strand affixed to a portion of clip 400), includes a pre-weakened breakaway portion at or near clip 400. By pulling back on the proximal end of retaining strand 404 while pushing out on middle tube 406 to close jaws 410A-B of clip 400 using ring 402, the pre-weakened portion of retaining strand 404 breaks at a predefined degree of tension. This releases closed clip 400. The proximal portion of retaining strand 404 is then removed. Middle tube 406 and catheter 106 are also withdrawn from brain 112. In another variation, distal end 118 of catheter 106 includes an inward extending longitudinal slot that is shaped to permit one of jaws 410A-B to spring outward toward its substantially open position even before clip 400 is extended out of lumen 114. This permits clip 400 to open around aneurysm 108 along the side of catheter 106 rather than concentrically outward.

Figure 6 is a schematic illustration of several alternative components for aneurysm-clipping in an aneurysm treatment device. In the examples of Figure 6, clip 600 includes distal hook 602 or other self-locking mechanism that avoids the need for a separate sliding ring 402 to close and/or retain clip 600 in its substantially closed position. In this example, clip 600 has a normally-open shape-memory property. Clip 600 may be delivered through catheter 106 and closed by a middle tube 406 or any other suitable technique.

Clip 604 includes another example of a self-locking mechanism, such as a ring 606 located at a distal end of one of its jaws. This self-locking mechanism moves (e.g., rotates) to engage the distal end of the opposing jaw to retain normally-open clip 604 in its substantially-closed position. Clip 604 may also be delivered through catheter 106 and closed by a middle tube 406 or other suitable technique.

Clip 608 is an example of a geared latch hook device that is delivered through catheter 106 and closed around a portion of aneurysm 108. In this example, clip 608 includes a body portion 610 and a hook portion 612. It also includes a resilient strand 614 or shaft that extends to proximal end 116 of catheter 106. By pushing on a proximal end of strand 614, curved hook portion 612 is closed around aneurysm 108. A distal portion of curved hook portion is

received by hole 616 in clip body 610. One or more teeth 618 on hook 612 engages a pawl-like device associated with hole 616, allowing hook 612 to clasp and retain aneurysm 108. Body 610 and strand 614 are releasably coupled to hook 612 by any suitable releasable fastening technique. Some suitable
5 examples include, by way of example, but not by way of limitation, a pre-weakened breakaway portion, a rotatably-releasable strand or shaft, and/or a threaded coupler.

Clip 620 is an example of another aneurysm clip or clasp that is delivered through catheter 106 and closed around aneurysm 108. In this example, clip 620
10 includes a body 622 portion and a hooked shaft 624 portion that operate together in a padlock-like fashion to clasp and retain aneurysm 108. Strand or shaft 626 engages hooked shaft 624 to pull it back, thereby clasping the desired portion of aneurysm 108 between hooked shaft 624 and body 622 of clip 620. Strand 626 releasably engages hooked shaft 624, such as by one of the above-described
15 releasable fastening techniques, or by simply receiving a hooked or other suitably shaped portion of a distal end of strand 626 in a slot or other suitable opening from which it can be disengaged by manipulating the proximal end of strand 626.

Clip 628 is an example of yet another aneurysm clip or clasp that is
20 delivered through catheter 106 and closed around aneurysm 108. In this example, clip 628 is a double bow-like clasp having a normally-closed shape-memory property. After being delivered through catheter 106, tension is applied to force its midregions outward so that aneurysm 108 can be positioned therebetween. One technique for applying such tension is to use one or more
25 resilient strands or shafts that releasably engage features on clip 628 (e.g., receptacles 630A-B). In an alternative example, clip 628 includes a normally-open shape-memory property. Such a normally-open clip 628 is closed around aneurysm 108 using a suitable closure technique, such as by using a middle tube 406 to push a surrounding ring 402 out around normally open clip 628 to close it
30 around aneurysm 108.

Figure 7 is a cross-sectional schematic diagram illustrating generally

another example of distal end 118 of catheter 106, the distal end 118 including a lumen 114 through which another example aneurysm treatment device 120 is disposed for treating aneurysm 108. In this example, aneurysm treatment device 120 includes a wire-like snare 700 having at least one strand that extends
5 through lumen 114 of catheter 106 from its proximal end 116 to its distal end 118, and extending outward from distal end 118 in a loop 702. In its substantially open position, as illustrated in Figure 7, loop 702 is large enough to encircle a desired portion of aneurysm 108. In this example, snare 700 extends through a unidirectional retention mechanism, such as cuff 704, in lumen 114 at
10 distal end 118 of catheter 106. In this example, cuff 704 includes two pieces 704A-B that lock when snare 700 is rotated after loop 702 is pulled snugly around aneurysm 108 to tie off aneurysm 108. In one example, snare 700 includes a pre-weakened breakaway portion that is slightly more proximal than cuff 704, so that when the user pulls firmly back on the proximal end of snare
15 700 with sufficient tension, snare 700 breaks away to leave behind loop 702, around aneurysm 108, and securing cuff 704. In this example, aneurysm treatment device 120 also includes a middle tube 406 having a lumen 408 through which a portion of snare 700 extends. The user pushes on the proximal end of middle tube 406 to push against cuff 704, while the proximal end of snare
20 700 is being pulled back, to break the pre-weakened portion of snare 700. Then, the user further pushes on the proximal end of middle tube 406 to push out and release cuff 704 and the tightened loop portion of snare 700. In an alternative example, in which snare 700 need not include a pre-weakened portion, cuff 704 includes a blade-like projection that cuts a portion of snare 700 to release loop
25 702 after it is secured around aneurysm 108. In addition to cuff 704, other modes of unidirectional retention devices operating noose-like loops 702 include a toothed or other structure operating similarly to a plastic cable-tie and/or a bag-tie, or a pawl or other ratcheting/escapement mechanism that allows loop 702 to be securely tightened around aneurysm 108.

30 Figure 8 includes several cross-sectional diagrams illustrating another example of a distal portion of a snare-like aneurysm treatment device 120 that

includes a strand **800**, the end of which has a normally-looped shape-memory property. In this example, strand **800** extends from proximal end **116** to distal end **118** of catheter **106** through its lumen **114**, through a central lumen of a middle tube **406**, and through a central lumen of ring **402**. A distal end of strand **800** is extended out from the distal end **118** of catheter **106** for a sufficient distance to allow its shape-memory property to hook the distal end of strand **800** around the desired portion of aneurysm **108**. In this example, the distal end of strand **800** includes a catch **802** (e.g., a ball, a grooved ball, a hook, or any other suitable structure). Catch **802** engages a more proximal portion of strand **800** after being hooked around the desired portion of aneurysm **108**. Middle tube **406** is then used to push ring **402** out over catch **402**. Then, the proximal end of strand **800** is pulled back to draw a noose-like loop to clamp off the desired portion of aneurysm **108**. In one example, strand **800** includes a more proximal pre-weakened portion that breaks away when sufficient tension is applied, leaving behind the loop and ring tying off aneurysm **108**. In an alternative example, a portion of strand **800** includes a toothed or other structure operating similarly to a plastic cable-tie and/or a bag-tie, or a pawl or other ratcheting/escapement mechanism, as discussed above, to retain the now-looped hook snare in its substantially closed position around aneurysm **108**. In another alternative example, ring **402** is omitted, and catch **802** includes a hook or other suitable structure that catches a more proximal portion of strand **800** when its proximal end is drawn back to break away a pre-weakened portion of strand **800** that is more proximal than the engaged hook.

Figure **9** is a perspective view illustrating another example of an aneurysm treatment device **900**. In this example, aneurysm treatment device **900** includes a pair of electrodes **902A-B** that are exovascularly delivered through lumen **114** of catheter **106**. In the illustration of Figure **9**, electrodes **902A-B** are elongate paddles extending outward from respective insulated stylet shafts **904A-B** at resiliently flexible outward necked portions **906A-B**. In this manner, when electrodes **902A-B** are extended out of lumen **114** at distal end **118** of catheter **106**, they spring outward into a substantially open position to allow

aneurysm **108** to be positioned therebetween. By then either sliding catheter **106** out over necked portions **906A-B**, or by then pulling back necked portions **906A-B** into lumen **114** at distal end **118** of catheter **106**, electrodes **902A-B** are forced together into a substantially closed position, clamping aneurysm **108** therebetween. Electrical energy is then applied between proximal ends of the insulated stylet shafts **904A-B** and conducted to electrodes **902A-B** to cauterize shut the clamped portion of aneurysm **108**. Electrodes **906A-B** are then again manipulated into their substantially open position and retracted together with catheter **106**.

10 Figure **10** is a perspective view illustrating another example of an aneurysm treatment device **1000** including a movable electrode and a fixed electrode. In this example, aneurysm treatment device **1000** includes a movable electrode **1002** extending out from lumen **114** at distal end **118** of catheter **106** on an electrically insulated stylet shaft **1004**. A flat fixed electrode **1006** is formed integrally with distal end **118** of catheter **106**, extending outwardly therefrom, with an associated conductor coupling it to proximal end **116** of catheter **106**. In this example, fixed electrode **1006** is first positioned adjacent to aneurysm **108**. Then, movable electrode **1002** is extended out around the other side of aneurysm **108**. In this example, movable electrode **1002** includes a rolling electrode that is rolled back and/or forth along aneurysm **108**, by manipulating a proximal end of shaft **1004**, to clamp the desired portion of aneurysm **108** between the electrodes **1002** and **1006** as electrical energy is applied to cauterize shut the desired portion aneurysm **108**.

25 Figure **11** is a perspective view illustrating another example of a catheter-delivered aneurysm treatment device, which in this case includes a C-channel clamp **1100** shaped for being fitted around a portion of blood vessel **110** and clamping a desired portion of aneurysm **108** therebetween. In one technique, C-channel clamp **1100** is mounted on the tip of a stylet shaft having a sufficient diameter to keep channel **1102** sufficiently open to slide around the desired portion of aneurysm **108** when the stylet shaft is extended out of distal tip **118** of catheter **106**. A second stylet (or a middle tube, such as middle tube **406**) is used

to slide C-channel clamp **1100** off the first stylet into place around vessel **110** and aneurysm **108**. In this example, C-channel clamp **1100** has a normally-closed shape-memory property, so that it closes around the desired portion of aneurysm **108** after it is slid into place off of the first stylet shaft. In a further
5 example, electrically insulative C-channel clamp **1100** also includes conductive electrodes **1104A-B** located along the edges of its C-channel for cauterizing closed the clamped portion of aneurysm **108**. In this example, electrodes **1104A-B** include receptacles, at any suitable location, for subsequent access by conductors delivering the electrical cautery energy after the delivery stylet(s) are
10 removed from lumen **114** of catheter **106**.

Figure **12** is a perspective view illustrating a number of possible variations of the minimally-invasive aneurysm treatment techniques discussed above, such as nasalpharyngeal access, frame-mounted entry devices, using a plurality of minimally-invasive devices, and/or using separate minimally-
15 invasive devices for imaging and aneurysm treatment. For example, while Figure **3** illustrated access through the top or the side of a patient's skull, Figure **12** illustrates a nasalpharyngeal node of access through a patient's nose and sinuses. In this example, a rotatable arc-like frame **1200** is mounted to a head holding device **1202**. One or more entry devices, such as ball-and-socket
20 trajectory-guide bearing entry devices **1204A-B**, is mounted to a suitable location on frame **1200**. In one example, such as illustrated in Figure **12**, a first entry device (e.g., entry device **1204A**) is used to provide an image-guided trajectory of a catheter-delivered aneurysm treatment device to a target aneurysm (for example, using the above-discussed clip, electrocautery electrodes, etc.). A
25 second entry device (e.g., entry device **1204B**) is used to establish a trajectory and introduce a minimally-invasive localized imaging modality (e.g., a microcoil for localized MRI, an endoscope for optical visualization, and ultrasound probe, etc.).

In the examples of Figures **1 - 12**, example materials suitable for
30 constructing catheter **106**, middle tube **406**, inner tube **405**, and/or cuff **704** include, by way of example, but not by way of limitation, one or a combination

of nonmagnetic carbon fiber, titanium, rigid or semi-rigid extruded plastic, polyetheretherketone (PEEK), and/or polyurethane. In a non-MR (e.g., CT) environment, in which nonmagnetic components are not required, stainless steel is also an example of a suitable material for these components. Example

5 materials suitable for constructing ring **402**, clip **400**, clip **600**, clip **604**, clip **608**, clip **620**, and/or clip **628** include, by way of example, but not by way of limitation, one or a combination of titanium, polyurethane, polyolefin, polyethylene, and/or polypropylene. Examples of suitable materials for constructing strand **404** and/or snare **700** include, by way of example, but not by

10 way of limitation, one or a combination of titanium, tungsten, platinum-iridium, an extruded plastic monofilament, nylon, and/or KEVLAR.[®] Moreover, strand **404** could be constructed from a twisted pair of strands constructed from the same or different ones of these or other materials. Examples of suitable materials for constructing hook/snare portion of strand **800** include, by way of

15 example, but not by way of limitation, nickel-titanium (nitinol) and/or other suitable nonmagnetic memory metal. Examples of suitable materials for constructing electrodes **902A-B**, electrode **1002**, electrode **1006**, and/or electrodes **1104A-B** include, by way of example, but not by way of limitation, one or a combination of platinum-iridium and/or other nonmagnetic conductive

20 material. Examples of suitable materials for constructing frame **1200** include, by way of example, but not by way of limitation, one or more of aluminum and/or other rigid nonmagnetic material.

It is to be understood that the above description is intended to be illustrative, and not restrictive. For example, the above-discussed embodiments

25 may be used in combination with each other. Many other embodiments will be apparent to those of skill in the art upon reviewing the above description. The scope of the invention should, therefore, be determined with reference to the appended claims, along with the full scope of equivalents to which such claims are entitled. In the appended claims, the terms “including” and “in which” are

30 used as the plain-English equivalents of the respective terms “comprising” and “wherein.”

WHAT IS CLAIMED IS:

1. A system including:
an elongate exovascular probe, including proximal and distal ends, the
5 probe including an outer dimension that is less than about 18 millimeters to
permit the probe to be introduced through a similarly-sized minimally-invasive
opening in a portion of a subject's skull and exovascularly advanced to an
aneurysm within the skull; and
an aneurysm treatment device carried by the probe and dimensioned to
10 permit the aneurysm treatment device to be introduced through the opening.
2. The system of claim 1, further including an imaging device to permit
viewing of an image of both the aneurysm treatment device and the aneurysm.
- 15 3. The system of claim 2, in which the imaging device includes a magnetic
resonance (MR) imaging device.
4. The system of claim 3, in which the imaging device further includes a
local MR imaging device near the distal end of the probe.
20
5. The system of claim 4, in which the local MR imaging device includes at
least one microcoil.
6. The system of claim 2, in which the imaging device includes a computed
25 tomography (CT) imaging device.
7. The system of claim 1, in which at least one of the aneurysm treatment
device and the distal end of the probe includes at least one of an MR or CT
imagable fiducial structure.
30
8. The system of claim 1, in which the probe and aneurysm treatment

device are both at least one of MR or CT compatible.

9. The system of claim 1, in which the aneurysm treatment device includes a structure having substantially open and substantially closed positions, wherein
5 the open position is sized to permit at least one portion of the aneurysm treatment device to be positioned around at least a portion of at least one of a saccular, globular, or giant aneurysm, and wherein the closed position is sized to permit the at least one portion of the aneurysm treatment device to press against at least a portion of the aneurysm.
- 10
10. The system of claim 9, in which the aneurysm treatment device structure includes a shape-memory property.
11. The system of claim 10, in which the shape-memory property, in the
15 absence of applied bias, is associated with one of the open or closed positions.
12. The system of claim 1, further including an elongate member shaped to extend through a lumen in the probe, the elongate member releasably coupling to the aneurysm treatment device.
- 20
13. The system of claim 1, in which the aneurysm treatment device is shaped to be extendable from and retractable into a lumen of the probe.
14. The system of claim 1, in which the aneurysm treatment device includes
25 at least one of a clip, a clasp, a snare, a loop, a hook, a staple, or an electrode.
15. The system of claim 14, in which the clip includes first and second electrodes.
- 30
16. The system of claim 1, in which the aneurysm treatment device includes a normally substantially open clip that is substantially closed when retracted into

a lumen of the probe, and further including:

- an elongate tube shaped to extend through the lumen of the probe, a distal end of the elongate tube shaped to extend out of the distal end of the probe and around a portion of the clip to substantially close a portion of the clip around
5 a portion of the aneurysm; and
a strand shaped to extend through the elongate tube, and releasably coupled to a portion of the clip.

17. The system of claim 16, further including a ring shaped to engage the
10 distal end of the elongate tube, the ring shaped to encircle a portion of the clip to hold the clip in the substantially closed position around the portion of the aneurysm.

18. The system of claim 1, in which the aneurysm treatment device includes
15 a snare shaped to extend through a lumen in the probe and to extend out from the distal end of the probe, the snare including a unidirectional retaining mechanism to retain the snare in a closed position after the snare has been positioned around a portion of an aneurysm.

20 19. The system of claim 18, in which the snare includes a breakaway portion to release a portion of the snare that has been positioned around the portion of the aneurysm.

20. The system of claim 1, in which the aneurysm treatment device includes
25 first and second electrodes, at least one of the first and second electrodes being shaped to extend through a lumen in the probe and to extend out from the distal end of the probe.

21. The system of claim 20, in which the first and second electrodes are
30 shaped to assume a substantially open position, to receive at least a portion of an aneurysm therebetween, when extended out from the distal end of the probe.

22. The system of claim 21, in which the first and second electrodes are also shaped to assume a substantially closed position, to pinch at least a portion of an aneurysm therebetween, when at least partially retracted back into the distal end of the probe.

5

23. The system of claim 20, in which one of the first and second electrodes includes a roller extendable out of the distal end of the probe.

24. The system of claim 1, further including an entry device, the entry device
10 including:

a first securing mechanism to secure the entry device in association with the subject's skull; and

a second securing mechanism to secure an orientation of a trajectory guide portion of the entry device to define a path between the minimally-
15 invasive opening and the aneurysm.

25. The system of claim 24, further including an imaging device to provide information upon which the orientation of the trajectory guide is determined.

20 26. A method including:

forming an opening in a subject's skull, the opening having a diameter that is less than or equal to the diameter of a burr hole;

exovascularly inserting a probe through the opening to an aneurysm using real-time or preoperative imaging to guide the probe to the aneurysm;

25 exovascularly introducing an aneurysm treatment device through a lumen in the probe to the aneurysm; and

altering a morphology of the aneurysm using the aneurysm treatment device.

30 27. The method of claim 26, in which the exovascularly inserting the probe through the opening to the aneurysm includes using at least one of magnetic

resonance (MR) or computed tomography (CT) imaging.

28. The method of claim 26, in which the exovascularly inserting the probe through the opening to the aneurysm includes visualizing three-dimensional
5 aspects of the aneurysm using computed tomography (CT) imaging.

29. The method of claim 26, in which the exovascularly inserting the probe through the opening to the aneurysm includes using a localized image obtained from an imaging device associated with a distal tip of the probe.
10

30. The method of claim 26, in which the altering the morphology of the aneurysm includes exovascularly pinching a portion of the aneurysm.

31. The method of claim 26, in which the altering the morphology of the
15 aneurysm includes applying electrical energy to a portion of the aneurysm.

32. A system including:

an elongate exovascular probe, including proximal and distal ends, the probe including an outer dimension that is less than about 18 millimeters to
20 permit the probe to be introduced through a similarly-sized minimally-invasive opening in a portion of a subject's skull and exovascularly advanced to an aneurysm within the skull;

an aneurysm treatment device carried by the probe and dimensioned to permit the aneurysm treatment device to be introduced through the opening; and
25 a local imaging device located near the distal end of the probe.

33. The system of claim 32, in which the local imaging device includes a magnetic resonance (MR) imaging device.

30 34. The system of claim 32, in which the aneurysm treatment device includes a structure having substantially open and substantially closed positions, wherein

the open position is sized to permit at least one portion of the aneurysm treatment device to be positioned around at least a portion of an aneurysm, and wherein the closed position is sized to permit the at least one portion of the aneurysm treatment device to press against at least a portion of the aneurysm.

5

35. The system of claim **32**, further including an entry device shaped to introduce the probe.

36. The system of claim **35**, in which the entry device includes:

10 a first securing mechanism to secure the entry device in association with the subject's skull; and

a second securing mechanism to secure an orientation of a trajectory guide portion of the entry device to define a path between the minimally-invasive opening and the aneurysm.




Fig.1




Fig.2




Fig.3

118






Fig. 4


5/12




(A) CLIP CLOSED AND RETRACTED



(B) CLIP OPEN AND EXTENDED



(C) CLIP CLOSED AROUND ANEURYSM



(D) RETAINER OPENED TO RELEASE CLIP

Fig.5

6/12




Fig.6

118




Fig. 7

8/12




Fig.8

9/12

900




Fig. 9

10/12




Fig. 10




Fig.11

12/12




Fig.12

INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 01/19629

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 A61B17/128 A61B17/122 A61B19/00 A61B18/14

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 706 668 A (BACKER) 17 November 1987 (1987-11-17) abstract; figures column 3, line 25-36	1, 9, 12, 14
Y		2-8, 10, 11, 13, 15-17, 20-22, 24, 25, 32-36
Y	WO 00 19927 A (REGENTS OF THE UNIVERSITY OF MINNESOTA) 13 April 2000 (2000-04-13) cited in the application the whole document	2-8, 24, 25, 32-36
	-/-	

☒ Further documents are listed in the continuation of box C.☒ Patent family members are listed in annex.

* Special categories of cited documents :

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *Z* document member of the same patent family

Date of the actual completion of the international search

14 November 2001

Date of mailing of the international search report

21/11/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Giménez Burgos, R

INTERNATIONAL SEARCH REPORT

ational Application No

rci/US 01/19629

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
Y	EP 0 326 426 A (JAPAN MEDICAL SUPPLY CO., LTD.) 2 August 1989 (1989-08-02) abstract; figures ----	10,11
Y	US 5 634 932 A (SCHMIDT) 3 June 1997 (1997-06-03) abstract; figures column 8, line 48 -column 9, line 45 column 2, line 19-54 ----	13,16,17
Y	US 5 201 900 A (NARDELLA) 13 April 1993 (1993-04-13) abstract; figures ----	15,20-22
A	US 5 174 276 A (CROCKARD) 29 December 1992 (1992-12-29) abstract; figures ----	1,9, 12-14
A	MARTIN: "VASCULAR MALFORMATIONS OF THE CNS: CEREBRAL ANEURYSMS" SURGERY, THE MEDICINE GROUP LTD., ABINGTON, GB, vol. 13, no. 6, 1 June 1995 (1995-06-01), pages 133-136, XP000506820 ISSN: 0263-9319 the whole document ----	1-3,7
A	US 6 024 695 A (TAYLOR ET AL.) 15 February 2000 (2000-02-15) abstract; figures ----	
A	US 6 019 724 A (GRONNINGSATER ET AL.) 1 February 2000 (2000-02-01) the whole document ----	
A	US 5 569 274 A (RAPACKI ET AL.) 29 October 1996 (1996-10-29) column 6, line 42-52; figures -----	1

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 01/19629

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 4706668	A	17-11-1987	NONE	
WO 0019927	A	13-04-2000	US 6195577 B1 AU 1109000 A EP 1121061 A1 WO 0019927 A1 US 2001014771 A1	27-02-2001 26-04-2000 08-08-2001 13-04-2000 16-08-2001
EP 0326426	A	02-08-1989	JP 1192367 A JP 2561853 B2 CA 1307885 A1 DE 68920055 D1 DE 68920055 T2 EP 0326426 A2 US 4950258 A	02-08-1989 11-12-1996 29-09-1992 02-02-1995 11-05-1995 02-08-1989 21-08-1990
US 5634932	A	03-06-1997	AU 7328296 A CA 2232995 A1 DE 19681595 T0 GB 2320199 A , B WO 9713466 A1 JP 11513292 T KR 271873 B1	30-04-1997 17-04-1997 15-10-1998 17-06-1998 17-04-1997 16-11-1999 01-12-2000
US 5201900	A	13-04-1993	NONE	
US 5174276	A	29-12-1992	GB 2226245 A WO 9005491 A2 JP 4501676 T	27-06-1990 31-05-1990 26-03-1992
US 6024695	A	15-02-2000	US 5950629 A US 5976156 A US 6231526 B1 US 5445166 A US 5695500 A US 5402801 A US 5630431 A US 6201984 B1 US 5279309 A	14-09-1999 02-11-1999 15-05-2001 29-08-1995 09-12-1997 04-04-1995 20-05-1997 13-03-2001 18-01-1994
US 6019724	A	01-02-2000	WO 9625882 A1 AU 4851396 A WO 9625881 A1	29-08-1996 11-09-1996 29-08-1996
US 5569274	A	29-10-1996	US 5452733 A AU 2777495 A WO 9600033 A1 AU 688303 B2 AU 6024594 A CA 2154354 A1 EP 0684781 A1 JP 8511694 T WO 9418881 A1 US 6283127 B1 US 5571215 A US 5425705 A US 5735290 A US 5613937 A	26-09-1995 19-01-1996 04-01-1996 12-03-1998 14-09-1994 01-09-1994 06-12-1995 10-12-1996 01-09-1994 04-09-2001 05-11-1996 20-06-1995 07-04-1998 25-03-1997

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/US 01/19629

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 5569274	A	US 6311693 B1	06-11-2001
		US 5536251 A	16-07-1996
		US 5797960 A	25-08-1998
		US 5713951 A	03-02-1998
		US 5728151 A	17-03-1998
		US 5718725 A	17-02-1998
		US 5682906 A	04-11-1997
		US 5766151 A	16-06-1998
		US 5799661 A	01-09-1998
		US 5961481 A	05-10-1999
		US 6010531 A	04-01-2000
		US 6079414 A	27-06-2000
		US 5814097 A	29-09-1998
		US 5855614 A	05-01-1999
		US 5823956 A	20-10-1998
		US 5829447 A	03-11-1998
		US 6029671 A	29-02-2000
		US 6125852 A	03-10-2000
		US 5855210 A	05-01-1999
		US 5814016 A	29-09-1998
		US 5980455 A	09-11-1999
		US 6027476 A	22-02-2000
		US 6161543 A	19-12-2000
		US 5972030 A	26-10-1999
		US 5924424 A	20-07-1999